



TECHNICAL DATA SHEET

PRODUCTION DESCRIPTION

Nimlac Emulsion is a water based high quality acrylic interior emulsion paint for decoration and protection of walls, ceilings and MDF partition that provides a smooth semi gloss finish. It has excellent hiding power, coverage and washability .

KEY BENIFITS

- Outstanding washability
- Superior Hiding Power
- Excellent Coverage
- No added lead or mercury

PRODUCT INFORMATION

Typical Use

For the Decoration ad protection of interior building surface

- Asbestos
- Cement
- Masonry
- plaster
- Brickworks Hard & Soft Boards

Pack size

1 Ltr, 4 Ltr, 10 Ltr,20 Ltr, Bulk

Colour Range

Standard Colour

Volume solids

50%

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, dry and free from all defective or poorly adhering material, grease, wax ,oils etc. After apply Nimlac Wall Filler 1 or 2 coats & finished the wall.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable surface preparation apply 1 or 2 coats of Nimlac Emulsion paint . Apply 2 coats of Nimlac Emulsion paint get finish with an appropriate paint system.

APPLICATION METHOD

The Product can be applied by Roller, Spray & Brush

Practical Coverage

1st coats 120 feet per liter
2nd coats 180 feet per liter

Drying Times

1st coat -20 minutes
2nd coats Apply After 6 Hours
