

ACRYLIC WALL FILLER



TECHNICAL DATA SHEET

PRODUCTION DESCRIPTION

Nimlac Wall Filler is interior plastered wall, concert or painted walls with outstanding fill up small holes & up dents. It provides the surface in perfections of surface with a smooth high quality finish. It will minimize the absorption and save the cost of the top coat paint.

KEY BENIFITS

- Acrylic Co-Polymer Water Base Primer matt paint.
- Quick Drying
- Good coverage

PRODUCT INFORMATION

Typical Use

It is suitable for all normal interior masonry surface including Brickwork, cement, asbestos, wall board & wood

Pack size

1 Liter, 4 Liter, 10 Liter, 20 Liter

Colour Range

White

SURFACE PREPARATION

Volume solids

Surface must be clear, dry and sound.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable surface preparation apply 1 or 2 coats of Nimlac Acrylic Wall Filler. Apply 2 coats of Nimlac Acrylic Wall Filler get finish with an appropriate paint system.

APPLICATION METHOD

Thinning depending on the method of application and if thinning necessary should not exceed 40% of fresh water.

The product can be applied by Roller, Spray & Brush.

Practical Coverage

1st coat 180 feet per liter

2nd 180 feet per liter

Drying Times

1st coat -20 minutes

2nd coat Apply After 6 Hours