

NIMLAC WEATHER PLUS(EXTERIOR)



TECHNICAL DATA SHEET

PRODUCTION DESCRIPTION

Nimlac weather Plus is an advanced all weather protection UV resistant exterior paint, based on acrylic Co-polymer Emulsion ,It is specially formulated using UV resistant pigments which is proven for algae, fungus, cracking, peeling. Fading and dirt pickup.

KEY BENIFITS

Excellent penetration in to the substrate three by providing the best adhesion offers best protection against alkali attack. Resistant to Algae & Fungus other benefit for paint, washability, free of lead mercury.

PRODUCT INFORMATION

Typical Use

For the Decoration ad protection of Exterior building surface

- Asbestos
- Cement
- Masonry
- plaster
- Brickworks Hard & Soft Boards

Pack size

1 Liter, 4 Liter, 10 Ltr,20 Liter, Bulk

Colour Range

Most Colours achievable

Volume solids

50%

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, dry and free from all defective or poorly adhering material, grease, wax, oils etc. Before apply Nimlac Wall Filler 1 or 2 coats & finished the wall.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. After suitable surface preparation apply 1 or 2 coats of Nimlac Emulsion paint. Apply 2 coats of Nimlac Emulsion paint get finish with an appropriate paint system.

APPLICATION METHOD

Cleaning Up

After Use, remove as much paint as Possible From brushes, rollers, and spray gum before clearing with water.

Drying Times

1st coat -30% of water
2nd coat- 25% of water
