

# CELLING WHITE



## TECHNICAL DATA SHEET

---

### PRODUCTION DESCRIPTION

Nimlac Ceiling White is recommended for use on properly prepared ceilings, it will provide the surface a smooth, durable, attractive finish. An economical Emulsion paint for painting of interior ceiling.

### KEY BENIFITS

- Excellent applicability
- Quick Drying
- High Opacity
- Good coverage

### PRODUCT INFORMATION

#### Typical Uses

For the decoration and painting of interior ceiling. It also can be used as primer prior to the application of Emulsion paint.

- Asbestos
- Cement
- Masonry
- Plaster
- Hard & soft Boards

#### Pack size

1 liter, 4 liter, 10 liter, 20 liters

#### Colour Range

White

#### Volume solids

### SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, dry and free from all defective or poorly adhering material, dirt, grease wax etc. After apply Nimlac Ceiling White 1 or 2 coats & finished the ceiling.

### SYSTEMS INFORMATION

**STIR THOROUGHLY BEFORE USE.** After suitable surface preparation apply 1 or 2 coats of Nimlac Ceiling White Apply 2 coats of Nimlac Ceiling White get finish with an appropriate paint system.

### APPLICATION METHOD

Dilute with clean water and should not exceed 35% by using fresh water.

The product can be applied by Roller & Brush.

#### Drying Times

Single coat at standard thickness 20-45 minutes  
Hard Drying 8-12 hours