

TECHNICAL DATA SHEET

PRODUCTION DESCRIPTION

NIMLAC Enamel is specially formulated and designed for all interior and exterior timber and metal applications where a gloss finish is desired. Enamel has high coverage, excellent opacity and is fast drying.

KEY BENEFITS

- Excellent washability
- Excellent Coverage
- self-leveling properties
- High Gloss

PRODUCT INFORMATION

Typical Uses

- Decorative paints with a wide colour range for coatings on wood, walls and steel gates.
- Also suitable for coatings on steelworks, pipelines and concrete.

Pack size

200ml, 500ml, 1 Ltr, 4 Ltr

Colour Range

Standard Colours

Volume solids

Approximately 50%

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry), and free from all defective or poorly adhering material, dirt, grease, wax. New or bare surfaces should be primed with an appropriate Nimlac Primer.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Apply 1 coat of the appropriate coloured Nimlac Undercoat, followed by 1 or 2 coats of High gloss. When a fast drying system

is required for new work, Quick Dry Wood Primer Undercoat (available in white only) can be used as an alternative.

Allow a minimum 6-8 hours for the undercoat to dry before applying the gloss finish. Where a second coat of High Gloss is required, allow a minimum of 16 hours between coats.

For improved obliteration on rough or textured surfaces, or when using special process colours 2 coats of High Gloss will be required in order to achieve full opacity.

TECHNICAL DATA SHEET

APPLICATION METHOD

NOTE: Whilst leading -edge technology has been used in the development of this product ,the nature of white solvent-based paints means that they will all discolour over time. The rate of discoloration is faster on areas with no or low natural or UV light. For longer lasting whiteness, we recommend the use of a water based formulation such as Quick Dry Gloss.

For best colour consistency, purchase sufficient tinted paint for each job including touch in at one time from the same source.

Brush or roller only. For Health & Safety a reason relating to all solvent -based paints, spray application is not recommended.

As with other solvent -based paints, do not apply in temperatures below 2⁰C.

Practical Coverage

On smooth surfaces of average porosity, a guide to the practical coverage which can be achieved is up to 18 m² per liter.

Spray Recommendations

This Product should not be sprayed.

Drying Times

Single coat at standard thickness:

Touch dry: 4-6 hours

Recoat: 16.24 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with brush cleaner.

When this paint container is empty please ask your stockiest about recycling .If you have leftover paint please, dispose of it responsibly.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost .To prevent spillage, please store and transport upright